



- 1 Connector for the UPS Battery Box connection 2 Extra Battery Box connector 3 Power socket for the battery charger circuit
4 Thermal Fuse protecting the battery charger circuit 5 Thermal switch for battery circuit

Main Specifications

- Internal battery charger on every unit
- Units can be expanded infinitely
- Batteries with thermal circuit protection
- Easy connection to UPS
- Convertible format (Tower or Rack 19")

Specifications

Model	BATTERY BOX FOR EVO DSP PLUS 3.600 RACK TOWER PF 0,9		
Code	FBBEDP3602RT/09		FBBEDP3602RT/18
Positioning	Into Tower or 19" Rack cabinet (2U) positioning		
Dimension (Box) WxHxD	43,8x8,8x63 cm		
Dimension (with packing) WxHxD	60x24x75 cm		
Weight	30 Kg		43 Kg
Battery			
Type	Lead acid, sealed, maintenance free		
Internal Battery Charger			
Nominal input voltage	230Vac		
Nominal input frequency	50/60Hz		
Nominal charging voltage	82,2Vdc		
Max charging current	1A		
Protection			
Battery charge input	Thermal fuse		
Battery circuit	Magnetothermic switch		
Environmental specification			
Working temperature	From 0 to 55 °C (recommended from 20 to 25 °C)		
Humidity	< 95% without condensation		
Maximum altitude	3000 m		
IP protection	IP20		
Certifications	CE		

© 2021 Tecnoware Power Systems. The technical data may change without prior notice.