

## KABELSCHLEPP cable carrier



order key: **0555.050.100.063-999**

quantity : **1**

### dimensions

|  |       |          |
|--|-------|----------|
| chain length Lk:                         | 999   | mm       |
| pitch:                                   | 55.50 | mm       |
| number of links n (incl. n reserve = ) : | 18    |          |
| number of stays nSt:                     | 18    |          |
| inner width Bi:                          | 100   | mm       |
| outer width Bk:                          | 122   | mm       |
| inside height hi:                        | 38.00 | mm       |
| link height hG:                          | 50.00 | mm       |
| bending radius KR:                       | 63.00 | mm       |
| self weight of chain :                   | 1.98  | kg/m     |
| self weight of chain total:              | 2     | kg       |
| :  |       | standard |

### end connectors

|                            |      |
|----------------------------|------|
| driver connection:         | with |
| connection of fixed point: | with |

### application parameters

|                        |                       |                  |
|------------------------|-----------------------|------------------|
| arrangement:           | given chain length Lk |                  |
| given chain length Lk: | 1000.00               | mm               |
| connection height H':  | 150.00                | mm               |
| total height H:        | 176.00                | mm               |
| weight of cables qz    | 0.10                  | kg/m             |
| max. acceleration a    | 1.00                  | m/s <sup>2</sup> |

max. velocity v

1.00 m/s

frequency

100 / h

© 2022 TSUBAKI KABELSCHLEPP GmbH, Wenden-Gerlingen